


J7
**ORFS mit
Überwurfmutter
45° Bogen**

 ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°


| Bestell-Nr. | | Schlauch ID | | | | Gewinde | A | B | E | W |
|-------------|-------------|-------------|-------|------|------|------------|-----|-----|----|----|
| Serie 46 | Serie 48 | DN | Zoll | Size | mm | UNF | mm | mm | mm | mm |
| 1J746-4-4 | 1J748-4-4 | 6 | 1/4 | -4 | 6,4 | 9/16x18 | 54 | 31 | 10 | 17 |
| 1J746-6-4 | 1J748-6-4 | 6 | 1/4 | -4 | 6,4 | 11/16x16 | 53 | 30 | 11 | 22 |
| 1J746-8-4 | 1J748-8-4 | 6 | 1/4 | -4 | 6,4 | 13/16x16 | 59 | 34 | 15 | 24 |
| 1J746-6-5 | 1J748-6-5 | 8 | 5/16 | -5 | 7,9 | 11/16x16 | 56 | 32 | 11 | 22 |
| 1J746-6-6 | 1J748-6-6 | 10 | 3/8 | -6 | 9,5 | 11/16x16 | 54 | 31 | 11 | 22 |
| 1J746-8-6 | 1J748-8-6 | 10 | 3/8 | -6 | 9,5 | 13/16x16 | 59 | 36 | 15 | 24 |
| 1J746-6-8 | | 12 | 1/2 | -8 | 12,7 | 11/16x16 | 57 | 33 | 11 | 22 |
| | 1J748-6-8 | 12 | 1/2 | -8 | 12,7 | 11/16 | 57 | 33 | 11 | 22 |
| 1J746-8-8 | 1J748-8-8 | 12 | 1/2 | -8 | 12,7 | 13/16x16 | 61 | 38 | 15 | 24 |
| 1J746-10-8 | 1J748-10-8 | 12 | 1/2 | -8 | 12,7 | 1x14 | 65 | 41 | 16 | 30 |
| 1J746-12-8 | 1J748-12-8 | 12 | 1/2 | -8 | 12,7 | 1 3/16x12 | 77 | 53 | 21 | 36 |
| 1J746-10-10 | 1J748-10-10 | 16 | 5/8 | -10 | 15,9 | 1x14 | 67 | 42 | 16 | 30 |
| 1J746-12-10 | 1J748-12-10 | 16 | 5/8 | -10 | 15,9 | 1 3/16x12 | 80 | 55 | 21 | 36 |
| 1J746-10-12 | 1J748-10-12 | 19 | 3/4 | -12 | 19,1 | 1x14 | 73 | 47 | 16 | 30 |
| 1J746-12-12 | 1J748-12-12 | 19 | 3/4 | -12 | 19,1 | 1 3/16x12 | 83 | 57 | 21 | 36 |
| 1J746-16-12 | 1J748-16-12 | 19 | 3/4 | -12 | 19,1 | 1 7/16x12 | 94 | 68 | 24 | 41 |
| 1J746-12-16 | 1J748-12-16 | 25 | 1 | -16 | 25,4 | 1 3/16x12 | 91 | 61 | 21 | 36 |
| 1J746-16-16 | 1J748-16-16 | 25 | 1 | -16 | 25,4 | 1 7/16x12 | 99 | 69 | 24 | 41 |
| 1J746-20-16 | 1J748-20-16 | 25 | 1 | -16 | 25,4 | 1 11/16x12 | 101 | 71 | 25 | 50 |
| 1J746-20-20 | | 31 | 1 1/4 | -20 | 31,8 | 1 11/16x12 | 124 | 86 | 26 | 50 |
| | 1J748-20-20 | 31 | 1 1/4 | -20 | 31,8 | 1 11/16x12 | 130 | 82 | 27 | 50 |
| | 1J748-24-24 | 38 | 1 1/2 | -24 | 38,1 | 2x12 | 148 | 110 | 40 | 60 |

 Geprüfte **Armaturenserien** für Schlauchtypen, je nach size:

Auch in Edelstahl erhältlich. Details siehe CAT 4400.1/DE

| | | | | | | | |
|-------------------|-------|-------|-------|-------|-------|------------|------------|
| 46 oder 48 | 441 | 461LT | 462 | 462TC | 462ST | 629PU | 692PU Twin |
| 46 | 463 | 492 | 492ST | 492TC | 692 | 692Twin | 692TC BCH1 |
| 48 | 301SN | 304 | 387 | 387ST | 387TC | 421RH | 421SN |
| | 426 | 421TC | 436 | 441RH | 462PU | 462PU Twin | BCH2 |
| | HT2 | ... | 471TC | 477 | 477ST | 477TC | 477RH |
| | 487 | 487ST | 487TC | 493 | 787 | 787TC | 787ST |
| | 797 | 797TC | 797ST | 811 | 881 | | |