


## FU JIS 30° Dichtkonus mit BSP-Überwurfmutter


ISO 228-1 – JIS B8363 – GUI



Bestell-Nr.		Schlauch ID				Gewinde BSP	A mm	B mm	H mm	W mm
Serie 46	Serie 48	DN	Zoll	Size	mm					
1FU46-4-4	1FU48-4-4	6	1/4	-4	6,4	1/4x19	50	32	19	19
1FU46-6-6	1FU48-6-6	10	3/8	-6	9,5	3/8x19	58	35	24	22
1FU46-12-12	1FU48-12-12	19	3/4	-12	19,1	3/4x14	71	45	36	36
1FU46-16-16	1FU48-16-16	25	1	-16	25,4	1x11	76	46	41	41

## GU JIS 60° Dichtkopf mit BSP-Überwurfmutter

ISO 228-1 – JIS B8363 – GUO



Bestell-Nr.		Schlauch ID				Gewinde BSP	A mm	B mm	H mm	W mm
Serie 46	Serie 48	DN	Zoll	Size	mm					
1GU46-4-4	1GU48-4-4	6	1/4	-4	6,4	1/4x19	55	33	19	19
1GU46-6-6	1GU48-6-6	10	3/8	-6	9,5	3/8x19	58	35	22	22
1GU46-8-8	1GU48-8-8	12	1/2	-8	12,7	1/2x14	55	32	27	27

Geprüfte **Armaturenserien** für Schlauchtypen, je nach size:

Auch in Edelstahl erhältlich. Details siehe CAT 4400.1/DE

<b>46</b> oder <b>48</b>	441	461LT	462	462TC	462ST	629PU	692PU Twin
<b>46</b>	463	492	492ST	492TC	692	692Twin	692TC BCH1
<b>48</b>	301SN	304	387	387ST	387TC	421RH	421SN
	426	421TC	436	441RH	462PU	462PU Twin	BCH2
	HT2	...	471TC	477	477ST	477TC	477RH
	487	487ST	487TC	493	787	787TC	787ST
	797	797TC	797ST	811	881		