

# TEKNOJET 2SC 400

EN 1829 - 2

 RECOMMENDED FOR:  
 PROFESSIONAL WATER JET CLEANERS

 RACCOMANDATO PER:  
 MACCHINE IDROPULTRICI PROFESSIONALI

**Alternative versions:**


 other colors available: BLUE, RED, GREY  
 altri colori disponibili: BLU, ROSSO, GRIGIO

**Features:**


Code	Hose size		Outside diameter		Max working pressure		Min burst pressure		Min bend radius		Weight	
	D.N.	Inch mm	Inch mm		PSI Bar		PSI Bar		Inch mm	Lb/ft kg/mt		
TJ2SC04	6	1/4" 6,4	0,53	13,4	5800	400	23200	1600	2,95	75	0,18	0,27
TJ2SC05	8	5/16" 7,9	0,59	15,0	5800	400	23200	1600	3,34	85	0,22	0,32
TJ2SC06	10	3/8" 9,5	0,67	17,0	5800	400	23200	1600	3,54	90	0,27	0,40
TJ2SC08	12	1/2" 12,8	0,8	20,4	5800	400	23200	1600	5,11	130	0,36	0,54


**TeknoJET 2SC 3/8"**

(9,5mm)

EN 1829-2

 -10°C / +150°C  
 14°F / +302°F

 400 Bar  
 40 MPa

**5800 Psi**

MARKING/MARCATURA: TRANSFER TAPE

**OPERATING**
**TEMPERATURE RANGE:**

 - 10°C/+135°C  
 (14°F to +275°F)  
 with peak of +150°C (302°F)

**TEMPERATURA**
**DI ESERCIZIO:**

 - 10°C/+135°C  
 (14°F / +275°F)  
 con punte di +150°C (302°F)

**TUBE:**

hot water, detergent and oil synthetic rubber

**SOTTOSTRATO:**

gomma sintetica resistente a acqua calda, detersivi e oli

**REINFORCEMENT:**

2 high tensile steel braids

**RINFORZO:**

2 trecce di acciaio ad alto carico

**COVER:**

synthetic rubber with extreme abrasion resistance

**COPERTURA:**

gomma sintetica con estrema resistenza all'abrasione

 Note: TO ORDER BLU VERSION PLEASE ADD "B" TO THE CODE  
 TO ORDER RED VERSION PLEASE ADD "R" TO THE CODE  
 TO ORDER GREY VERSION PLEASE ADD "G" TO THE CODE  
 TO ORDER FOREVER VERSION  PLEASE ADD "FV" TO THE CODE