


Armaturen
 10356 – 10656


**518C • 520N/528N • 53DM • 540N • 550H • 55LT •
 560TJ • 580N/588N • 590TJ • 53DM • 2040N • 2040H**

10356 – Einschraubzapfen SAE (JIC) 37°


WERKSTOFF Stahl, verzinkt, transparent Cr(VI)-frei passiviert.
 Weitere Werkstoffe auf Anfrage.

Artikelnummer #	DN size mm Zoll				Anschlussart		A mm	B mm	H mm	Max. WP MPa
	DN	size	mm	Zoll	Gewindegröße	Rohr AD Zoll				
10356-4-4-SM	6	-04	6,4	1/4	7/16 - 20 UNF	1/4	51,3	26,8	14	41,0
10356-5-5-SM	8	-05	7,9	5/16	1/2 - 20 UNF	5/16	52,5	26,7	14	41,0
10356-6-5-SM	8	-05	7,9	5/16	9/16 - 18 UNF	3/8	54,8	29,0	19	34,5
10356-6-6-SM	10	-06	9,5	3/8	9/16 - 18 UNF	3/8	54,6	29,4	19	34,5
10356-8-6-SM	10	-06	9,5	3/8	3/4 - 16 UNF	1/2	57,2	37,0	22	34,5
10356-8-8-SM	12	-08	12,7	1/2	3/4 - 16 UNF	1/2	60,5	32,1	22	34,5

10656 – SAE (JIC) 37° Dichtkegel mit Überwurfmutter UNF-Überwurfmutter


WERKSTOFF Stahl, verzinkt, transparent Cr(VI)-frei passiviert.
 Weitere Werkstoffe auf Anfrage.

Artikelnummer #	DN size mm Zoll				Anschlussart		A mm	B mm	H mm	J mm	Max. WP MPa
	DN	size	mm	Zoll	Gewindegröße	Rohr AD Zoll					
10656-4-2	3	-02	3,2	1/8	7/16 - 20UNF	1/4	33	16,0	13	17	41,0
10656-4-3-SM	5	-03	4,8	3/16	7/16 - 20 UNF	1/4	45,2	27,5	12	17	41,0
10656-4-4-SM	6	-04	6,4	1/4	7/16 - 20 UNF	1/4	52,0	27,5	14	17	41,0
10656-5-4-SM	6	-04	6,4	1/4	1/2 - 20 UNF	5/16	53,7	29,2	14	17	41,0
10656-6-4-SM	6	-04	6,4	1/4	9/16 - 18 UNF	3/8	54,2	29,7	14	19	34,5
10656-5-5-SM	8	-05	7,9	5/16	1/2 - 20 UNF	5/16	56,0	20,3	14	17	41,0
10656-6-5-SM	8	-05	7,9	5/16	9/16 - 18 UNF	3/8	56,6	30,8	14	19	34,5
10656-6-6-SM	10	-06	9,5	3/8	9/16 - 18 UNF	3/8	56,3	31,2	17	19	34,5
10656-8-6-SM	10	-06	9,5	3/8	3/4 - 16 UNF	1/2	60,2	35,0	19	22	34,5
10656-8-8-SM	12	-08	12,7	1/2	3/4 - 16 UNF	1/2	64,4	36,0	22	22	34,5
10656-10-8-SM	12	-08	12,7	1/2	7/8 - 14 UNF	5/8	67,1	38,8	22	27	34,5
10656-12-12-SM	20	-12	19,0	3/4	1 1/16-12 UNF	3/4	77,8	43,9	27	32	34,5
10656-16-16-SM	25	-16	25,4	1	1 5/16 - 12 UNF	1	97,0	48,9	32	41	27,5

Armaturen