


E

 518C • 520N/528N • 53DM • 540N • 550H • 55LT •
 560TJ • 580N/588N • 590TJ • 53DM • 2040N • 2040H


 Armaturen
19256 – 1B156

19256 – 60° Dichtkegel mit BSP-Überwurfmutter


WERKSTOFF Stahl, verzinkt, transparent Cr(VI)-frei passiviert.
 Weitere Werkstoffe auf Anfrage.

Artikelnummer #	DN size mm Zoll				Anschlussart		A mm	B mm	J mm	Max. WP MPa
	size	mm	Zoll	Gewindegröße	Rohr AD Zoll					
19256-4-3	5	-03	4,8	3/16	G1/4	1/4	34,8	17,1	19	63,0
19256-4-4	6	-04	6,4	1/4	G1/4	1/4	41,8	17,3	19	63,0
19256-6-4	6	-04	6,4	1/4	G3/8	3/8	44,9	20,4	22	55,0
19256-4-5	8	-05	7,9	5/16	G1/4	1/4	47,1	21,3	19	63,0
19256-6-5	8	-05	7,9	5/16	G3/8	3/8	46,2	20,4	22	55,0
19256-6-6	10	-06	9,5	3/8	G3/8	3/8	45,9	20,7	22	55,0
19256-8-6	10	-06	9,5	3/8	G1/2	1/2	48,0	22,8	27	43,0
19256-8-8	12	-08	12,7	1/2	G1/2	1/2	51,2	22,8	27	43,0
19256-12-12	20	-12	19,0	3/4	G3/4	3/4	60,3	26,4	32	35,0
19256-16-16	25	-16	25,4	1	G1	1	73,6	25,5	41	28,0

1B156 – 60° Dichtkegel mit BSP-Überwurfmutter 45° Bogen


WERKSTOFF Stahl, verzinkt, transparent Cr(VI)-frei passiviert.
 Weitere Werkstoffe auf Anfrage.

Artikelnummer #	DN size mm Zoll				Anschlussart		A mm	B mm	E mm	J mm	Max. WP MPa
	size	mm	Zoll	Gewindegröße	Rohr AD Zoll						
1B156-4-3	5	-03	4,8	3/16	G1/4	1/4	57	39,3	15,5	19	63,0
1B156-4-4	6	-04	6,4	1/4	G1/4	1/4	62	38,0	15,0	19	63,0
1B156-6-5	8	-05	7,9	5/16	G3/8	3/8	65	39,0	17,0	22	55,0
1B156-6-6	10	-06	9,5	3/8	G3/8	3/8	67	42,0	17,0	22	55,0
1B156-8-8	12	-08	12,7	1/2	G1/2	1/2	77	48,0	20,0	27	43,0

Armaturen