



**E**

 518C • 520N/528N • 53DM • 540N • 550H • 55LT •  
 560TJ • 580N/588N • 590TJ • 53DM • 2040N • 2040H

 Armaturen  
 13756 – 13956

**13756 – SAE (JIC) 37° Dichtkonus mit Überwurfmutter**  
 45° Bogen – UNF-Überwurfmutter

**WERKSTOFF** Stahl, verzinkt, transparent Cr(VI)-frei passiviert.  
 Weitere Werkstoffe auf Anfrage.

Artikelnummer #	DN				Anschlussart		A mm	B mm	E mm	J mm	Max. WP MPa
	size	mm	Zoll	Gewindegröße	Rohr AD Zoll						
13756-4-3-SM	5	-03	4,8	3/16	7/16 - 20 UNF	1/4"	55,4	37,7	10	17	41,0
13756-4-4-SM	6	-04	6,4	1/4	7/16 - 20 UNF	1/4"	55,8	31,3	10	17	41,0
13756-6-6-SM	10	-06	9,5	3/8	9/16 - 18 UNF	3/8"	65,0	40,1	11	19	34,5
13756-8-8-SM	12	-08	12,7	1/2	3/4 - 16 UNF	1/2"	69,2	40,8	15	22	34,5
13756-16-16-SM	25	-16	25,4	1	1 5/16 - 12 UNF	1"	120,0	72,0	24	41	27,5

**13956 – SAE (JIC) 37° Dichtkonus mit Überwurfmutter**  
 90° Bogen – UNF-Überwurfmutter

**WERKSTOFF** Stahl, verzinkt, transparent Cr(VI)-frei passiviert.  
 Weitere Werkstoffe auf Anfrage.

Artikelnummer #	DN				Anschlussart		A mm	B mm	E mm	J mm	Max. WP MPa
	size	mm	Zoll	Gewindegröße	Rohr AD Zoll						
13956-4-3-SM	5	-03	4,8	3/16	7/16 - 20 UNF	1/4"	44,4	26,7	21	17	41,0
13956-4-4-SM	6	-04	6,4	1/4	7/16 - 20 UNF	1/4"	51,0	26,5	21	17	41,0
13956-6-4-SM	6	-04	6,4	1/4	9/16 - 18 UNF	3/8"	51,0	26,5	23	19	34,5
13956-6-6-SM	10	-06	9,5	3/8	9/16 - 18 UNF	3/8"	56,0	30,7	23	19	34,5
13956-8-6-SM	10	-06	9,5	3/8	3/4 - 16 UNF	1/2"	65,0	39,5	29	22	34,5
13956-8-8-SM	12	-08	12,7	1/2	3/4 - 16 UNF	1/2"	63,0	34,6	29	22	34,5
13956-10-8-SM	12	-08	12,7	1/2	7/8 - 14 UNF	5/8"	71,0	42,0	32	27	34,5
13956-16-16-SM	25	-16	25,4	1	1 5/16 - 12 UNF	1"	110,8	63,0	56	41	27,5

Armaturen