


E

 518C • 520N/528N • 53DM • 540N • 550H • 55LT •
 560TJ • 580N/588N • 590TJ • 53DM • 2040N • 2040H


 Armaturen
1D956 – 10156

1D956 – BSP-Einschraubzapfen zylindrisch DIN 3852 Form A


WERKSTOFF Stahl, verzinkt, transparent Cr(VI)-frei passiviert.
 Weitere Werkstoffe auf Anfrage.

Artikelnummer #	DN size mm Zoll				Anschlussart		A mm	B mm	H mm	Max. WP MPa
	DN	size	mm	Zoll	Gewindegröße	Rohr AD Zoll				
1D956-4-3	5	-03	4,8	3/16	G1/4	1/4	44,4	26,7	19	63,0
1D956-4-4	6	-04	6,4	1/4	G1/4	1/4	51,5	27,0	19	63,0
1D956-6-5	8	-05	7,9	5/16	G3/8	3/8	53,0	27,2	22	55,0
1D956-6-6	10	-06	9,5	3/8	G3/8	3/8	52,9	27,7	22	55,0
1D956-8-8	12	-08	12,7	1/2	G1/2	1/2	60,0	31,6	27	43,0
1D956-12-12	20	-12	19,0	3/4	G3/4	3/4	75,1	41,2	32	35,0
1D956-16-16	25	-16	25,4	1	G1	1	90,5	42,4	41	28,0

10156 – NPTF-Einschraubzapfen


WERKSTOFF Stahl, verzinkt, transparent Cr(VI)-frei passiviert.
 Weitere Werkstoffe auf Anfrage.

Artikelnummer #	DN size mm Zoll				Anschlussart		A mm	B mm	H mm	Max. WP MPa
	DN	size	mm	Zoll	Gewindegröße	Rohr AD Zoll				
10156-2-2	3	-02	3,2	1/8	1/8 - 27NPTF	1/8	35,0	18,0	13	34,5
10156-2-3-SM	5	-03	4,8	3/16	1/8 - 27 NPTF	1/8	40,4	22,7	14	83,0
10156-4-3-SM	5	-03	4,8	3/16	1/4 - 18 NPTF	1/4	44,9	27,2	17	34,5
10156-4-4-SM	6	-04	6,4	1/4	1/4 - 18 NPTF	1/4	52,0	27,5	17	34,5
10156-4-5-SM	8	-05	7,9	5/16	1/4 - 18 NPTF	1/4	53,5	27,3	17	34,5
10156-4-6-SM	10	-06	9,5	3/8	1/4 - 18 NPTF	1/4	55,0	27,8	17	34,5
10156-6-6-SM	10	-06	9,5	3/8	3/8 - 18 NPTF	3/8	55,0	29,8	19	27,5
10156-8-8-SM	12	-08	12,7	1/2	1/2 - 14 NPTF	1/2	63,0	34,6	24	24,0
10156-12-12-SM	20	-12	19,0	3/4	3/4 - 14 NPTF	3/4	75,4	41,5	32	21,0
10156-16-16-SM	25	-16	25,4	1	1 - 11 1/2 NPTF	1	93,6	45,5	41	17,0

Armaturen