

Medium Pressure  
 Standard

 Parkrimp No-Skive Hose  
 492

## 492

### Elite No-Skive Compact

EN 857 1SC – ISO 11237 Type 1SC



- **No-Skive** hose construction
  - Compact design
- Nitrile (NBR) inner tube
  - extended fluid compatibility
- Exceeding EN/ISO specifications for pressure, bend radius and abrasion resistance

#### Primary Applications

Demanding medium pressure hydraulic applications

#### Type Approvals

 Details please find on pages **Ab-16** to **Ab-19**

#### Applicable Specifications

EN 857 1SC – ISO 11237 Type 1SC

#### Construction

Inner tube: Nitrile (NBR)  
 Reinforcement: One high-tensile steel wire braid  
 Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C  
 Water ..... max. +85 °C

#### Recommended Fluids

Hydraulic fluids on a mineral-oil basis, water-glycol and lubricating oils, air and water. For air and gas applications with a pressure exceeding 1.7 MPa, the cover must be pin-pricked.

 Consult the chemical compatibility section on pages **Ab-26** to **Ab-34** for more detailed information.

#### Fitting Series



Part Number	Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	DN	Inch	Size	mm		max. working pressure MPa	psi	min. burst pressure MPa	psi		
492-4	6	1/4	-4	6.4	11.5	28.0	4060	112.0	16240	75	0.18
492-5	8	5/16	-5	7.9	13.6	25.0	3625	100.0	14500	85	0.21
492-6	10	3/8	-6	9.5	15.5	22.5	3260	90.0	13050	90	0.25
492-8	12	1/2	-8	12.7	18.9	19.0	2755	76.0	11020	130	0.33
492-10	16	5/8	-10	15.9	22.2	15.0	2175	60.0	8700	150	0.41
492-12	19	3/4	-12	19.1	26.0	15.0	2175	60.0	8700	180	0.56
492-16	25	1	-16	25.4	33.3	11.0	1595	44.0	6380	230	0.75
492-20-WR	31	1 1/4	-20	31.8	40.0	7.5	1085	30.0	4350	335	0.93

Part Number without a suffix: the hose cover has a smooth appearance. Part Number with a suffix (WR): the hose cover has a wrapped appearance.  
 The combination of high temperature and high pressure could reduce the hose life.  
 Also available in reels up to size -16 under part number 492-xx-RL.

#### Hose layline example

**Parker** ▶ Elite ◀ 492-6 WP 22,5 MPa (3260 PSI) | - - 10 mm (3/8) ISO11237/EN857 1SC 10 Made in Italy



Cab-28

Catalogue 4400/UK

Archivierung: 11/2022