

BALWASH 28/4.0K - BLUE

10.1W0K.B



EN 1829-2

Isobaric high pressure, one steel braid reinforced powerwash hose

REFERENCE	#	DN	inch	SAE Dash	ID mm	OD mm	MPa PSI	MPa PSI	MIN BEND RAD mm	KG kg/m
BALWASH 28/4.0K - BLUE	10.1W0K.04B	DN06	1/4"	-04	6.4	11.6	28.0 4000	70.0 10000	55	0.16
BALWASH 28/4.0K - BLUE	10.1W0K.05B	DN08	5/16"	-05	8.0	13.6	28.0 4000	70.0 10000	60	0.21
BALWASH 28/4.0K - BLUE	10.1W0K.06B	DN10	3/8"	-06	9.8	15.4	28.0 4000	70.0 10000	65	0.24
BALWASH 28/4.0K - BLUE	10.1W0K.08B	DN12	1/2"	-08	12.7	19.0	28.0 4000	70.0 10000	80	0.36

INNER TUBE: seamless hot water resistant synthetic rubber

REINFORCEMENT: 1 high tensile steel wire braid

OUTER TUBE: blue-wrapped pin-pricked synthetic rubber, resistant to oil, weather, and abrasion

SAFETY FACTOR: 2.5:1

TEMPERATURE RANGE: Continuous service: 0°C (+32°F) to +155°C (+311°F)

APPLICATION: Professional pressure cleaning equipment

COUPLINGS: Balflex® 2-piece fittings, Series 23 with Series 20 ferrules- Balflex® Multicrimp fittings, Series BW23/BF21

COVER: Standard, high abrasion

NOTE: Hose Construction: Compact

BALFLEX >> **BALWASH 28/4K** 155°C / 311°F -04 DN06 1/4" - WP 28.0 MPa 4000 PSI